



AQUAKYD LG | DECKING OIL

Solvent-Based Decking Oil
Chemstuk Pty Ltd

Description

Decking Oil is a premium solvent-based timber coating designed to revitalise, protect, and enhance exterior timber surfaces. It penetrates deeply into wood fibres while providing a durable protective layer, delivering a natural wet-look finish. Formulated with high solids and UV-resistant technology, it protects timber from weathering, moisture, and environmental damage.

Recommended Uses

- Timber decking
- Outdoor furniture
- Pergolas and fences
- Exterior timber cladding
- General exterior wood surfaces

Key Features

- Enhances natural timber colour
- Wet-look finish
- Deep penetration into timber
- UV resistant
- Weather and moisture protection
- High solids formulation
- Extends the life of timber
- Easy application

Physical Properties

Colour	Tinted (various colours available)
Finish	Semi-gloss / Wet look
Type 12 months at 25°C	Solvent-based alkyd polyurethane oil
Coverage	Up to 60 m ² per 10L (depending on timber)
Specific Gravity	~0.9–1.1 kg/L
VOC	<450 g/L
Shelf Life	12 months at 25°C

Application Conditions

Apply in well-ventilated conditions. Do not apply when the temperature is below 10°C or above 35°C, or when humidity exceeds 80%.

Application Method

Brush / Roller / Applicator pad

Thinner: Not recommended (ready to use)

Cleaning: Mineral turpentine or suitable solvent

Drying Times (25°C)

Touch Dry	8 hours
Recoat	12–24 hours
Full Cure	3–5 days

Surface Preparation

Ensure timber is clean, dry, and free from dust, grease, mould, and previous coatings—sand-weathered timber to restore the surface before application.

Storage

Store in a cool, dry place between 5°C and 35°C. Keep the container tightly sealed and away from ignition sources.

DISCLAIMER

This Technical Data Sheet is to be used as a guide only; it is NOT a specification. Chemstuk Pty Ltd has no control over the use or storage of this product and therefore does not accept liability in this regard. Any verbal advice given should not be regarded as authoritative information. This information is subject to change without notice; all applicators should ensure they have current information. This product is intended for the use only of skilled tradesmen and, where applicable, statutorily licensed tradesmen experienced and trained in the use of this product. Due to differences in substrates, application methods and local conditions, purchasers of these products must ensure that they are suitable for their specific application before using these products. While the information contained in the TDS and SDS is accurate to the best of our knowledge, Chemstuk Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the company's liability in relation to defective products shall be limited to replacement of the product if the product is proven to be defective.