



- Durable and wear-resistant
- Easy application by roller or brush
- Suitable for interior and exterior use
- Optional anti-slip additive available (Grip711)

BETONSEAL AU 845

High Gloss Concrete Sealer (Clear)

Product Description

BETON SEAL AU845 is a premium, solvent-based acrylic concrete sealer designed to provide a durable, high-gloss protective finish. It enhances the natural appearance of concrete while delivering long-lasting protection against water, UV exposure, and general wear.

Recommended Uses

- Driveways
- Exposed aggregate concrete
- Patios and outdoor areas
- Garage floors
- Decorative concrete surfaces
- Refurbishment of aged concrete

Key Features & Benefits

- High gloss finish enhances surface appearance
- UV-resistant – non-yellowing performance
- Water resistant – reduces moisture ingress

Technical Data

Property	Value
Appearance	Clear
Finish	Gloss
Solids Content	30 ± 2 %
Specific Gravity	0.99 kg/L
VOC	< 380 g/L
Flash Point	32°C

Recommended DFT ~100 microns

Coverage Rate

Approximately **8–10 m² per litre**, depending on surface porosity and texture.

Drying & Recoating (at 25°C)

Stage	Time
Touch Dry	~1 hour
Recoat	1–18 hours
Light Traffic	24 hours
Full Cure	7 days

Surface Preparation

All surfaces must be clean, dry and free from dust, oil, grease, curing compounds or previous coatings.

Concrete must comply with:

- Minimum strength: 25 MPa
- Moisture level: $\leq 75\%$ RH (ASTM F2170 / AS1884)

Do not apply to surfaces affected by rising damp.

Application

Apply using a roller or a brush.

Thinning (if required):

EX-T-1 up to 10%

Application Conditions:

- Ambient temperature: 10°C – 35°C
- Relative humidity: <80%
- Surface temperature must be at least 4°C above dew point

Film Thickness

Typical application:

- Wet film thickness: 200–250 microns
- Dry film thickness: ~100 microns

Storage & Shelf Life

- Shelf life: 12 months (unopened)
- Store between 5°C and 35°C
- Keep in a cool, dry place away from direct sunlight

Packaging

Available in:

- 15 L
- 20 L

Safety

This product is flammable. Use only in well-ventilated areas. Avoid inhalation of vapours and contact with skin or eyes.

Refer to the Safety Data Sheet (SDS) for full safety and handling information.

Additional Notes

- Coverage rate and drying times may vary depending on environmental conditions and substrate porosity.
- Always apply a test patch prior to full application.
- Anti-slip performance can be improved using the Grip711 additive.

DISCLAIMER

This Technical Data Sheet is to be used as a guide only; it is NOT a specification. Chemstuk Pty Ltd has no control over the use or storage of this product and therefore does not accept liability in this regard. Any verbal advice given should not be regarded as authoritative information. This information is subject to change without notice; all applicators should ensure they have current information. This product is intended for the use only of skilled tradesmen and, where applicable, statutorily licensed tradesmen experienced and trained in the use of this product. Due to differences in substrates, application methods and local conditions, purchasers of these products must ensure that they are suitable for their specific application before using these products. While the information contained in the TDS and SDS is accurate to the best of our knowledge, Chemstuk Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the company's liability in relation to defective products shall be limited to replacement of the product if the product is proven to be defective.