

CHEMSTUK



CINDOPOX DEEP EP 134

Two-Component Epoxy Casting Resin
Chemstuk Pty Ltd

1. Identification

Product Name: CINDOPOX DEEP EP-134
Recommended Use: Epoxy deep casting, bonding and coating system
Supplier: Chemstuk Pty Ltd, Thomastown VIC, Australia
Emergency Contact: Poisons Information Centre 13 11 26 / Emergency 000

2. Hazard Identification

GHS Classification:
Skin Irritation – Category 2 (H315)
Skin Sensitiser – Category 1 (H317)
Eye Irritation – Category 2A (H319)

Signal Word: WARNING

3. Composition / Information on Ingredients

Part A: Epoxy resin
Part B: Amine hardener
Additives

4. First Aid Measures

Inhalation: Move to fresh air.
Skin Contact: Wash thoroughly with soap

and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

5. Fire Fighting Measures

Suitable Media: Foam, CO₂, dry chemical.
Hazards: May emit toxic fumes under fire conditions.
Protective Equipment: Self-contained breathing apparatus.

6. Accidental Release Measures

Contain spill and absorb with inert material.
Prevent entry into drains or waterways.

7. Handling and Storage

Avoid skin contact and inhalation of vapours.
Use appropriate PPE.
Store between 5–35°C in sealed containers.

8. Exposure Controls / Personal Protection

Ensure adequate ventilation.
Wear gloves, goggles and protective clothing.

Exposure Limits:
Epoxy components: Refer to Safe Work Australia standards

9. Physical and Chemical Properties

Appearance: Clear liquid
Odour: Mild

Flash Point: Not applicable
Density: Part A ~1.1 kg/L, Part B ~0.9 kg/L
VOC: 0 g/L

10. Stability and Reactivity

Stable under normal conditions.
Avoid heat, moisture and oxidisers.

11. Toxicological Information

May cause skin sensitisation and irritation.
Irritating to the eyes.

12. Ecological Information

Avoid environmental release.
May be harmful to aquatic life.

13. Disposal Considerations

Dispose of according to local regulations.
Do not discharge into drains.

14. Transport Information

UN Number: 1760 (hardener component)
Class: 8
Packing Group: III
Hazchem Code: 2X

15. Regulatory Information

Complies with Safe Work Australia GHS requirements.

16. Other Information

Issue Date: 2026
Revision: EP 134 / REV 5