



Liquid Lastic 242

Two-Component Polyurethane
Waterproofing Membrane
Chemstuk Pty Ltd

1. Identification

Product Name: Liquid Lastic 242
Recommended Use: Polyurethane
waterproofing membrane and protective
coating
Supplier: Chemstuk Pty Ltd, Thomastown
VIC, Australia
Emergency Contact: Poisons Information
Centre 13 11 26 / Emergency 000

2. Hazard Identification

Part A:

- Skin Irritation – Category 2
- Eye Irritation – Category 2A
- Skin Sensitiser – Category 1

Part B:

- Flammable Liquid – Category 3
- Skin Irritation – Category 2
- Respiratory Sensitiser – Category 1

Signal Word: WARNING

3. Composition / Information on Ingredients

Part A: Polyurethane resin
Part B: Isocyanate hardener
Additives and solvents

4. First Aid Measures

Inhalation: Move to fresh air immediately.
Skin Contact: Wash thoroughly with soap
and water.
Eye Contact: Rinse cautiously with water
for at least 15 minutes.
Ingestion: Seek immediate medical
advice.

5. Fire Fighting Measures

Suitable Media: Foam, CO₂, dry chemical.
Hazards: Flammable vapours may form
explosive mixtures.
Protective Equipment: SCBA required.

6. Accidental Release Measures

Remove ignition sources.
Contain spill with inert absorbent.
Prevent entry into drains or waterways.

7. Handling and Storage

Use appropriate PPE and adequate
ventilation.
Store sealed between 5–35°C away from
moisture and ignition sources.

8. Exposure Controls / Personal Protection

Wear gloves, goggles and protective
clothing.
Respirator recommended in confined
spaces.
Ensure adequate ventilation.

9. Physical and Chemical Properties

Appearance: Greyish liquid

Finish: Gloss

Flash Point: ~28°C

VOC: <90 g/L

Density:

Part A ~1.6 kg/L

Part B ~0.9 kg/L

10. Stability and Reactivity

Stable under normal conditions.

Avoid heat, sparks, moisture and oxidising agents.

11. Toxicological Information

May cause irritation and sensitisation.

Harmful if inhaled in confined spaces.

12. Ecological Information

Avoid environmental release.

Harmful to aquatic life in large quantities.

13. Disposal Considerations

Dispose according to local regulations.

Do not discharge into drains.

14. Transport Information

UN Number: 1263

Class: 3

Packing Group: III

Hazchem Code: 3Y

15. Regulatory Information

Complies with Safe Work Australia GHS requirements.

16. Other Information

Issue Date: 2026

Revision: 242 / REV 2