



naNo-Leak FC 111

Water-Based Silicone Waterproofing
Coating

Chemstuk Pty Ltd

Description

naNo-Leak FC 111 is a high-performance waterproofing coating based on advanced silicone water-based resin technology. It is designed to provide superior water repellency, breathability, and long-term protection for concrete and masonry surfaces.

Recommended Uses

- Concrete walls and facades
- Roof tiles and cement sheets
- Exterior masonry surfaces
- Waterproofing membranes
- Protective coating for porous substrates

Key Features

- Excellent water repellency
- Breathable coating (vapour permeable)
- UV resistant
- Eco-friendly and low VOC
- Easy application
- Suitable for Australian conditions

Physical Properties

Colour: Clear / Slight milky

CHEMSTUK Pty Ltd
1/11 Industrial Avenue
Thomastown
Tel: +61 3 9936 0531
www.chemstuk.com.au

Finish: N/A

Solids by Volume: ~15%

Specific Gravity: ~1.05 kg/L

VOC: <90 g/L

Shelf Life: 12 months at 25°C

Application Conditions

Do not apply when relative humidity exceeds 80% or when the substrate temperature is less than 3°C above the dew point.

Application Method

Airless spray / Air spray / Brush / Roller

Thinner: Water (max 10–20%)

Cleaning: Water

Coverage

Approx. 18 m²/L depending on substrate porosity

Film Thickness

Dry Film Thickness: ~15–25 microns

Wet Film Thickness: ~80–120 microns

Drying Times (25°C)

Touch Dry: 30–60 minutes

Recoat: 2–4 hours

Full Cure: 24 hours

Surface Preparation

Surfaces must be clean, dry, and free from dust, grease, oil, and loose materials. Concrete should be sound and properly cured before application.

Storage

Store between 5°C and 35°C in a dry, shaded environment. Protect from freezing and contamination.

DISCLAIMER

This Technical Data Sheet is to be used as a guide only; it is NOT a specification. Chemstuk Pty Ltd has no control over the use or storage of this product and therefore does not accept liability in this regard. Any verbal advice given should not be regarded as authoritative information. This information is subject to change without notice; all applicators should ensure they have current information. This product is intended for the use only of skilled tradesmen and, where applicable, statutorily licensed tradesmen experienced and trained in the use of this product. Due to differences in substrates, application methods and local conditions, purchasers of these products must ensure that they are suitable for their specific application before using these products. While the information contained in the TDS and SDS is accurate to the best of our knowledge, Chemstuk Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the company's liability in relation to defective products shall be limited to replacement of the product if the product is proven to be defective.