



## **PRIMIT E6-111**

Two-Component Epoxy Primer  
Chemstuk Pty Ltd

### **1. Identification**

Product Name: PRIMIT E6-111  
Recommended Use: Two-component epoxy primer for concrete and steel  
Supplier: Chemstuk Pty Ltd, Thomastown VIC, Australia  
Emergency Contact: Poisons Information Centre 13 11 26 / Emergency 000

### **2. Hazard Identification**

GHS Classification:  
Flammable Liquid – Category 3 (H226)  
Skin Irritation – Category 2 (H315)  
Skin Sensitiser – Category 1 (H317)  
Eye Irritation – Category 2A (H319)

Signal Word: WARNING

### **3. Composition / Information on Ingredients**

Epoxy resin (Part A)  
Polyamine hardener (Part B)  
Solvents and additives

### **4. First Aid Measures**

Inhalation: Move to fresh air immediately.  
Skin Contact: Wash thoroughly with soap and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

### **5. Fire Fighting Measures**

Suitable Media: Foam, CO<sub>2</sub>, dry chemical.  
Hazards: Flammable vapours may form explosive mixtures.  
Protective Equipment: Self-contained breathing apparatus.

### **6. Accidental Release Measures**

Remove ignition sources.  
Contain spill and absorb with inert material.  
Prevent entry into drains or waterways.

### **7. Handling and Storage**

Avoid inhalation of vapours.  
Use appropriate PPE.  
Store between 5–35°C away from ignition sources.

### **8. Exposure Controls / Personal Protection**

Engineering Controls: Ensure adequate ventilation.  
PPE: Gloves, safety goggles, protective clothing.  
Respiratory Protection: Use a respirator if ventilation is inadequate.

Exposure Limits:  
Solvent vapours: Refer to relevant exposure standards

### **9. Physical and Chemical Properties**

Appearance: Clear liquid  
Odour: Mild solvent

Flash Point: ~28°C  
Density: ~0.99 kg/L  
VOC: <560 g/L

## **10. Stability and Reactivity**

Stable under normal conditions.  
Avoid heat, sparks, and strong oxidisers.

## **11. Toxicological Information**

May cause skin irritation and sensitisation.  
Irritating to the eyes.

## **12. Ecological Information**

Avoid release into the environment.  
It may be harmful to aquatic life.

## **13. Disposal Considerations**

Dispose of contents and container in accordance with local regulations.  
Do not discharge into drains.

## **14. Transport Information**

UN Number: 1263  
Class: 3  
Packing Group: III  
Hazchem Code: 3Y

## **15. Regulatory Information**

Complies with GHS and Safe Work Australia requirements.

## **16. Other Information**

Issue Date: 2026  
Revision: Chemstuk Standard