

PRIMIT E6-111 — Part A (Base)

Epoxy Resin Base Component

Chemstuk Pty Ltd

1. Identification

Product Name: PRIMIT E6-111 — Part A (Base)

Recommended Use: Base component of a two-component epoxy primer for concrete and steel

Supplier: Chemstuk Pty Ltd, Thomastown VIC, Australia

Emergency Contact: Poisons Information Centre 13 11 26 / Emergency 000

2. Hazard Identification

GHS Classification:

Flammable Liquid – Category 3 (H226)

Skin Irritation – Category 2 (H315)

Eye Irritation – Category 2A (H319)

Signal Word: WARNING

Hazard Statements: H226 Flammable liquid and vapour; H315 Causes skin irritation; H319 Causes serious eye irritation.

3. Composition / Information on Ingredients

Epoxy resin

Solvents and additives

4. First Aid Measures

Inhalation: Move to fresh air immediately.

Skin Contact: Wash thoroughly with soap and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

5. Fire Fighting Measures

Suitable Media: Foam, CO₂, dry chemical.

Hazards: Flammable vapours may form explosive mixtures.

Protective Equipment: Self-contained breathing apparatus.

6. Accidental Release Measures

Remove ignition sources.

Contain spill and absorb with inert material.

Prevent entry into drains or waterways.

7. Handling and Storage

Avoid inhalation of vapours.

Use appropriate PPE.

Store between 5–35°C away from ignition sources.

8. Exposure Controls / Personal Protection

Engineering Controls: Ensure adequate ventilation.

PPE: Gloves, safety goggles, protective clothing.

Respiratory Protection: Use a respirator if ventilation is inadequate.

9. Physical and Chemical Properties

Appearance: Clear liquid

Odour: Mild solvent

Flash Point: ~28°C

Density: Part A 1.1Gr/Cm3

10. Stability and Reactivity

Stable under normal conditions.

Avoid heat, sparks, and strong oxidisers.

11. Toxicological Information

May cause skin and eye irritation.

12. Ecological Information

Avoid release into the environment.

May be harmful to aquatic life.

13. Disposal Considerations

Dispose of contents and container in accordance with local regulations.

Do not discharge into drains.

14. Transport Information

UN Number: 1263

Class: 3 (Flammable Liquid)

Packing Group: III

Hazchem Code: 3Y

This classification applies to Part A (Base) only. Part B (Hardener) is classified separately — see the Part B Safety Data Sheet.

15. Regulatory Information

Complies with GHS and Safe Work Australia requirements.

16. Other Information

Issue Date: 2026

Revision: E6-111 / REV 6 (Part A)

CHEMSTUK Pty Ltd

1/11 Industrial Avenue

Thomastown

Tel: +61 3 9936 0531

www.chemstuk.com.au