

PRIMIT E6-111 — Part B (Hardener)

Polyamide Hardener Component (Curing Agent 114-CA)

Chemstuk Pty Ltd

1. Identification

Product Name: PRIMIT E6-111 — Part B (Hardener)

Recommended Use: Hardener component of a two-component epoxy primer for concrete

Supplier: Chemstuk Pty Ltd, Thomastown VIC, Australia

Emergency Contact: Poisons Information Centre 13 11 26 / Emergency 000

2. Hazard Identification

GHS Classification:

Skin Irritation – Category 2 (H315) rather than merely irritant; verify against the actual curing agent 114-CA classification]

Skin Sensitiser – Category 1 (H317)

Eye Irritation – Category 2A (H319)

Signal Word: DANGER

Hazard Statements: H315 Causes skin irritation; H317 May cause an allergic skin reaction; H319 Causes serious eye irritation.

3. Composition / Information on Ingredients

Polyamide hardener (Curing Agent 114-CA)

[Chemstuk to confirm exact composition and CAS numbers.]

4. First Aid Measures

Inhalation: Move to fresh air immediately.

Skin Contact: Remove contaminated clothing. Wash thoroughly with soap and water. Seek medical advice if irritation persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Seek urgent medical attention.

Ingestion: Do NOT induce vomiting. Seek immediate medical assistance.

5. Fire Fighting Measures

Suitable Media: Foam, CO₂, dry chemical.

Hazards: Category 3

Protective Equipment: Self-contained breathing apparatus.

6. Accidental Release Measures

Contain spill and absorb with inert material.

Prevent entry into drains or waterways.

Avoid skin and eye contact with spilled material.

7. Handling and Storage

Avoid inhalation of vapours.

Use appropriate PPE, including eye and skin protection.

Store between 5–35°C in sealed containers.

8. Exposure Controls / Personal Protection

Engineering Controls: Ensure adequate ventilation.

PPE: Chemical-resistant gloves, safety goggles/face shield, protective clothing.

Respiratory Protection: Use a respirator if ventilation is inadequate.

9. Physical and Chemical Properties

Appearance: Liquid

Flash Point: 28 °

Density: .9 gr/cm³

10. Stability and Reactivity

Stable under normal conditions.

Reacts with acids; may react with moisture over time.

Avoid heat and strong oxidisers.

11. Toxicological Information

Skin sensitiser; may cause allergic skin reaction.

May cause skin and eye irritation, potentially more severe than Part A

12. Ecological Information

Avoid release into the environment.

May be harmful to aquatic life.

13. Disposal Considerations

Dispose of contents and container in accordance with local regulations.

Do not discharge into drains.

14. Transport Information

UN 1263, Class 3, Flammable Liquid

15. Regulatory Information

Complies with GHS and Safe Work Australia requirements.

16. Other Information

Issue Date: 2026

Revision: E6-111 / REV 6 (Part B)

CHEMSTUK Pty Ltd

1/11 Industrial Avenue

Thomastown

Tel: +61 3 9936 0531

www.chemstuk.com.au