

CHEMSTUK



PRIMKYD ALKYD PRIMER

Chemstuk Pty Ltd

Product Description

Primkyd Alkyd Primer is a high-quality, air-drying alkyd primer designed for metal and wood surfaces. It provides excellent adhesion, corrosion resistance and a smooth base for subsequent topcoats.

Recommended Uses

- Metal surfaces
- Steel structures
- Wood surfaces
- Interior and exterior applications

Key Features & Benefits

- Excellent adhesion to prepared substrates
- Good corrosion resistance
- Fast drying
- Compatible with alkyd topcoats
- Smooth finish

Technical Data

Finish: Gloss / Matt (depending on system)

Solids by Volume: $\sim 35 \pm 2\%$

Coverage: $\sim 8-10 \text{ m}^2/\text{L}$ at 40 microns

Flash Point: $\sim 38^\circ\text{C}$

Specific Gravity: $\sim 1.2 \text{ kg/L}$

VOC: $<450 \text{ g/L}$

Application

Apply by spray, roller or brush.

Thinning: Use suitable thinner up to 10–20% depending on method.

Drying Times (20°C)

Touch Dry: ~ 1 hour

Hard Dry: ~ 4 hours

Full Cure: ~ 3 days

Surface Preparation

Surface must be clean, dry and free from contaminants such as oil, grease and rust. Priming is recommended before applying topcoat.

Storage & Shelf Life

12 months shelf life. Store between $5-35^\circ\text{C}$.

Safety

Refer to SDS before use.

DISCLAIMER

This Technical Data Sheet is to be used as a guide only; it is NOT a specification. Chemstuk Pty Ltd has no control over the use or storage of this product and therefore does not accept liability in this regard. Any verbal advice given should not be regarded as authoritative information. This information is subject to change without notice; all applicators should ensure they have current information. This product is intended for the use only of skilled tradesmen and, where applicable, statutorily licensed tradesmen experienced and trained in the use of this product. Due to differences in substrates, application methods and local conditions, purchasers of these products must ensure that they are suitable for their specific application before using these products. While the information contained in the TDS and SDS is accurate to the best of our knowledge, Chemstuk Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the company's liability in relation to defective products shall be limited to replacement of the product if the product is proven to be defective.