

CHEMSTUK



WALKYD LW-835

Odourless Oil-Based Gloss Paint

Chemstuk Pty Ltd

1. Identification

Product Name: WALKYD LW-835

Recommended Use: Oil-based gloss coating for interior and exterior surfaces

Supplier: Chemstuk Pty Ltd, Thomastown VIC, Australia

Emergency Contact: Poisons Information Centre 13 11 26 / Emergency 000

2. Hazard Identification

GHS Classification:

Flammable Liquid – Category 3 (H226)

Skin Irritation – Category 2 (H315)

Eye Irritation – Category 2A (H319)

Signal Word: WARNING

3. Composition / Information on Ingredients

Alkyd resin (long oil)

Hydrocarbon solvents (mineral turpentine)

Pigments and additives

4. First Aid Measures

Inhalation: Move to fresh air immediately.

Skin Contact: Wash thoroughly with soap and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

5. Fire Fighting Measures

Suitable Media: Foam, CO₂, dry chemical.

Hazards: Flammable liquid and vapour.

Protective Equipment: Self-contained breathing apparatus.

6. Accidental Release Measures

Remove ignition sources.

Contain spill and absorb with inert material.

Prevent entry into drains or waterways.

7. Handling and Storage

Avoid inhalation of vapours.

Use appropriate PPE.

Store in a cool, well-ventilated area away from ignition sources.

8. Exposure Controls / Personal Protection

Ensure adequate ventilation.

Wear gloves, goggles and protective clothing.

Respirator recommended in confined spaces.

Exposure Limits:

Hydrocarbon solvents: Refer to Safe Work Australia standards

9. Physical and Chemical Properties

Appearance: Glossy liquid

Odour: Mild solvent

Flash Point: ~38–45°C

Density: ~1.2 kg/L

VOC: <76 g/L

10. Stability and Reactivity

Stable under normal conditions.

Avoid heat, sparks, and oxidisers.

11. Toxicological Information

May cause irritation to the skin and eyes.

Prolonged exposure may affect the respiratory system.

12. Ecological Information

Avoid environmental release.

Harmful to aquatic life in large quantities.

13. Disposal Considerations

Dispose of contents and container in accordance with local regulations.

Do not discharge into drains.

14. Transport Information

UN Number: 1263

Class: 3

Packing Group: III

Hazchem Code: 3Y

15. Regulatory Information

Complies with Safe Work Australia GHS requirements.

16. Other Information

Issue Date: 2026

Revision: LW 835 / REV 5